

Cat 5e、Cat 6 無遮蔽90度防塵蓋資訊插座

Cat5e、Cat6非屏蔽90度含防塵門資訊插座適用於資訊桌盒埋入式面板及19"空白面板用，現場依T568A或T568B配線方式安裝，本產品採特殊防塵門設計，除了IDC與線對連結時阻抗更小外也無卡門困擾，有效防止未使用之插座侵入灰塵。



符合標準

- ◆ ANSI/TIA-568-C.2 Cat.5e
- ◆ ANSI/TIA-568-C.2 Cat.6
- ◆ ISO/IEC 2nd Edition 11801 CLASS E
- ◆ CENELEC EN 50173-1, CENELEC EN 50288-6-1,
- ◆ IEC 61156-5 for horizontal cable
- ◆ Flame Retardancy is verified according to IEC 60332-1-2.
- ◆ RoHS compliance for the requirement

產品應用





- ◆ 10BASE-T, 100BASE-TX, 1000BASE-T Fast Ethernet (IEEE 802.3)
- ◆ 100 VG - AnyLAN(IEEE802.12), 1.2/2.4 Mbps ATM
- ◆ 1.2/2.4Gbps ATM
- ◆ Voice, T1, ISDN

產品特色

傳輸頻寬：250MHz	符合UL 94V-0防火等級規範制定
絕緣耐壓：1000V RMS for 1min	接觸阻抗：20 mΩ per contact
絕緣阻抗：500 MΩ	金針材質：底材磷青銅，鍍100μ"鎳後，鍍上50μ"金
額定電壓及電流：150VAC，1.5 Amps	端子插拔次數：750 次
PCB 電路板材質：FR-4, 厚度 1.6mm	◎額定溫度 -40°C -75°C

產品效能

Length (ft), Limit 295	(Pair 45)	292
Prop. Delay (ns), Limit 498		453
Delay Skew (ns), Limit 44	(Pair 78)	23
Resistance (ohms)		Open
Insertion Loss Margin (dB)	(Pair 12)	2.3
Frequency (MHz)	(Pair 12)	250.0
Limit (dB)	(Pair 12)	31.1



訂購資訊

ALKJ.5eUVS.OR	CAT5e UTP Keystone 90 degree blue housng with shutter
ALKJ.5eUVS.WH	CAT5e UTP Keystone 90 degree orange housng with shutter
ALKJ.5eUVS.WH	CAT5e UTP Keystone 90 degree white housng with shutter
ALKJ.6UVS.BU	CAT6 UTP Keystone 90 degree blue housng with shutter
ALKJ.6UVS.OR	CAT6 UTP Keystone 90 degree orange housng with shutter
ALKJ.6UVS-WH	CAT6 UTP Keystone 90 degree white housng with shutter