

Cat6、Cat6A 極細網路跳接線



產品特色

- ◆ 4對RJ45-RJ45跳線線徑為28AWG~30AWG
- ◆ 插拔次數大於750次以上且不影響效能
- ◆ 跳線採用原廠充膠製造之成型跳線以確保整體傳輸品質
- ◆ 符合耐燃等級，其阻燃及低煙霧標準需依據IEC 60332-1[1,2]

Impedance	64kHz	125Ω ± 20%		
	1~250MHz	100Ω ± 15%		
Attenuation & Near End Cross Talk	Frequency (MHz)	Min. Insertion Loss (dB)	Min. Next (dB)	Min. PS Next (dB)
	1 MHz	3.15	74.3	72.3
	10 MHz	8.85	59.3	57.3
	100 MHz	28.65	44.3	42.3
	200 MHz	41.4	39.8	37.8
	250 MHz	46.65	38.3	36.3
	300 MHz	51.45	37.1	35.1
	400 MHz	60.15	35.3	33.3
	500 MHz	67.95	33.8	31.8

訂購資訊

AL-CAT6_PATCHCORD1M_30AWG	Cat6 1米 30AWG極細 跳接線
AL-CAT6_PATCHCORD2M_30AWG	Cat6 2米 30AWG極細 跳接線
AL-CAT6_PATCHCORD3M_30AWG	Cat6 3米 30AWG極細 跳接線
AL-CAT6A_PATCHCORD1M_32AWG	Cat6A 1米 32AWG極細 跳接線
AL-CAT6A_PATCHCORD2M_32AWG	Cat6A 2米 32AWG極細 跳接線
AL-CAT6A_PATCHCORD3M_32AWG	Cat6A 3米 32AWG極細 跳接線